

TRETRICE PLUMBING PRODUCTS

800B UTILITY GAUGE



The Trerice 800B Utility Gauge is designed for general pressure indication requirements. This gauge provides excellent accuracy (1.6% full scale) and reliability at an economical cost. The case is drawn steel and wetted parts are brass.

SPECIFICATIONS	800B UTILITY GAUGE	
Model	800B	
Dial Sizes	1 1/2" (40mm), 2" (50mm), 2 1/2" (63mm), 4" (100mm)	
Wetted Parts	Bronze tube, brass socket	
Movement	Brass	
Connection	1/8 NPT (not available with 4" dial size) 1/4 NPT (not available with 1 1/2" dial size)	
Case	Drawn steel, black finished, stem-mounted flangeless	
Window	Acrylic	
Pointer	Steel, black painted	
Dial Face	Aluminum, white background with black graduations and markings	
Accuracy	1.6% Full Scale	
Maximum Temperature	180° F (82° C)	
Approximate Shipping Weight	1 1/2": 0.2 lbs. (0.09 kg)	2": 0.3 lbs. (0.14 kg)
	2 1/2": 0.3 lbs. (0.14 kg)	4": 0.6 lbs. (0.27 kg)

How To Order (Example 800B 2502 L A 110)

Model	Dial Size		Connection Size		Connection Location		Units of Measure		Range Code
800B	15	1 1/2"	01	1/8 NPT	L	Lower	A	psi	See Range Table
	20	2"	02	1/4 NPT	B	Back	D	psi/kPa	
	25	2 1/2"							
	40	4"							

Range Codes	Specific Ranges	Range Codes	Specific Ranges	Range Codes	Specific Ranges
010	30" Hg to 0	080	0 to 15 psi	150	0 to 400 psi
020	30" Hg to 15 psi	090	0 to 30 psi	160	0 to 600 psi
030	30" Hg to 30 psi	100	0 to 60 psi	180	0 to 1000 psi
040	30" Hg to 60 psi	110	0 to 100 psi	190	0 to 1500 psi
050	30" Hg to 100 psi	120	0 to 160 psi	200	0 to 2000 psi
060	30" Hg to 150 psi	130	0 to 200 psi	210	0 to 3000 psi
070	30" Hg to 300 psi	140	0 to 300 psi	220	0 to 5000 psi

